

Mecal S.r.l.
Strada per Felizzano 18
I- 15043 Fubine (AL)
ph. +39 0131 792792
fax +39 0131 792733/4
www.mecal.net



TBP Carrier Strip Cutter



Specifications

ID
TBP

PART NUMBER
871600060

AIR PRESSURE
5-7 BAR

DIMENSION (mm)
W 105 x H 130 x D 90

DIMENSION (")
W 4.13 x H 5.12 x D 3.54

WEIGHT
2.6 Kg (5.77 lb)



Cutting the carrier strip while crimping (both semi-automatically with a bench-top press fitted with an SC 11 stripper-crimper or automatically with a cut and strip machine) is not suggested, as the consequent production of off-cuts would put the whole system at risk of jamming. Placing the TBP pneumatic carrier cutter beside the crimping unit allows the carrier strip to be chopped dropping, the scrap out of the way. The TBP cutter can handle carrier strip thickness up to 1.5mm.

A special external pneumatic actuating kit must be used to fit the TBP cutter to a crimping press (normally Mecal TT, P107 or PE4).

Produced under a quality Management System certified to ISO 9001 (TUV).

Specifications subject to change. Consult Mecal S.r.l. for latest specifications.

Mecal S.r.l.
Strada per Felizzano 18
I- 15043 Fubine (AL)
ph. +39 0131 792792
fax +39 0131 792733/4
www.mecal.net



TBPR Heavy-Duty Carrier Strip Cutter



Specifications

ID
TBPR

PART NUMBER
871600072

AIR PRESSURE
5-7 BAR

DIMENSION (mm)
W 105 x H 197 x D 90

DIMENSION (")
W 4,13" x H 7,75" x D 3,54"

WEIGHT
2,8 Kg (6,22 lb)



Azienda con Sistema Qualità
certificato N° 501001810



Cutting the carrier strip while crimping (both semi-automatically with a bench-top press fitted with an SC 11 stripper-crimper or automatically with a cut and strip machine) is not suggested, as the consequent production of off-cuts would put the whole system at risk of jamming. Placing the TBPR pneumatic carrier cutter beside the crimping unit allows the carrier strip to be chopped dropping the scrap out of the way. The TBPR cutter can handle carrier strip thickness above 1.5mm. A special external pneumatic actuating kit must be used to fit the TBPR cutter to a crimping press (normally Mecal PE4 or P104).

Produced under a quality Management System certified to ISO 9001 (TUV).

Specifications subject to change. Consult Mecal S.r.l. for latest specifications.